



# FS Chester

Single fired floor tiles



FS Chester



# FS Chester

Single fired floor tiles

FS Comillas

# FS Chester

Single fired floor tiles




FS CHESTER



FS COMILLAS


## FS CHESTER



6 patterns

45 * 45 * 1,05 cm   18 * 18"	
NO RECTIFIED	NATURAL
FS CHESTER	BN14
	21009

## FS COMILLAS



8 patterns

33 * 33 * 0,95 cm   13 * 13"	
NO RECTIFIED	NATURAL
FS COMILLAS	BN14
	20933

### CARACTERÍSTICAS TÉCNICAS | TECHNICAL CHARACTERISTICS

joint	versatile	matt	diferent shades	shade variation	various graphics

### CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO | ANTI-SLIP CHARACTERISTICS

Ensayo   Essay	Características   Features	Resultado   Result	
		CHESTER	COMILLAS
DIN 51130	Ángulo crítico (Pies calzados)   Critical angle (footwear)	R9	R10
DIN 51097	Ángulo crítico (Pies descalzos)   Critical angle (Wet loaded barefoot)	-	A+B
BS 7976-2	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test-PTV)		+36Wet
UNE-ENV 12633	Antideslizamiento (Test del péndulo)   Slip resistance (Pendulum test)	Class 1	Class 2
ANSI A.1371	Coefficiente de Fricción Dinámico   Dynamic Coefficient of Friction (DCOF)	-	>0,42
ISO 10545-7	Resistencia a la Abrasión Superficial/ Resistance to Surface Abrasion	PEI 4	PEI 4

### EMBALAJE | PACKING

(Los pesos aquí reflejados pueden sufrir ligeras variaciones en función del lote de producción. Weights shown here may slightly vary depending on the production lot.)

Formato   Sizes	Cajas   Boxes			Pallet			Tamaño cm aprox.	Cont./20' m2/ sq.m	Cont./20' m2/ sq.m
	Piezas	m2/ sq.m	kg	Cajas	m2/ sq.m	kg			
cm									
45 * 45 * 1,05	5	1	23,139	66	66	1551	120 * 80 * 105	914,89	1021,28
33 * 33 * 0,95	10	1,09	22,92	48	52,32	1124	120 * 80 * 81	1055,23	1177,94
inch	Units	ft2	lb	Boxes	ft2	lb	Sizes inch approx.	ft2	ft2
17 11/16 * 17 11/16 * 7/16	5	10,76	51,02	66	710,42	3419,96	47 1/4 * 31 1/2 * 41 5/16	9847,91	10993,02
13 * 13 * 3/8	10	11,73	50,52	48	563,17	2477,99	47 1/4 * 31 1/2 * 31 7/8	11358,54	12679,31